AMENDMENT OF SOLICIT	TATION/MODIFI	CATION OF CONTRACT	1. CONTRAC	T ID CODE	PAGE OF	PAGES
AMENDMENT OF BOLICE		CITION OF CONTRACT	J		1	3
2. AMENDMENT/MODIFICATION NO.	3. EFFECTIVE DATE	4. REQUISITION/PURCHASE REQ. NO.		5. PROJECT	NO.(If applic	able)
0003	20-Jan-2006					
6. ISSUED BY CODE	W912P8	7. ADMINISTERED BY (If other than item 6)	CC	ODE		
USACE, CONTRACTING DIVISION ATTN: CEMVN-CT, ROOM 172 7400 LEAKE AVE. NEW ORLEANS LA 70118-3651		See Item 6				
8. NAME AND ADDRESS OF CONTRACTOR (No., Street, County, State and		, State and Zip Code)	x 9A. AMENDA W912P8-06-F	A. AMENDMENT OF SOLICITATION NO V912P8-06-R-0090		
			X 9B. DATED (13-Jan-2006			
			10A. MOD. O	F CONTRAC	CT/ORDER	NO.
CODE	Et dir imir dor		10B. DATED	(SEE ITEM	13)	
CODE 11.	FACILITY COI THIS ITEM ONLY A	DE I PPLIES TO AMENDMENTS OF SOLI	CITATIONS			
X The above numbered solicitation is amended as set for		Г	is extended,	X is not exte	nded.	
Offer must acknowledge receipt of this amendment (a) By completing Items 8 and 15, and returning or (c) By separate letter or telegram which includes RECEIVED AT THE PLACE DESIGNATED FOR REJECTION OF YOUR OFFER. If by virtue of this provided each telegram or letter makes reference to	copies of the amendme a reference to the solicitation THE RECEIPT OF OFFER amendment you desire to ch	nt; (b) By acknowledging receipt of this amendm on and amendment numbers. FAILURE OF YOU S PRIOR TO THE HOUR AND DATE SPECIFI ange an offer already submitted, such change ma	ent on each copy of the UR ACKNOWLEDGM IED MAY RESULT IN y be made by telegram	e offer submitte ENT TO BE N	d;	
12. ACCOUNTING AND APPROPRIATION I	OATA (If required)					
		O MODIFICATIONS OF CONTRACTS				
A. THIS CHANGE ORDER IS ISSUED PUT CONTRACT ORDER NO. IN ITEM 10A	RSUANT TO: (Specif	T/ORDER NO. AS DESCRIBED IN IT y authority) THE CHANGES SET FOR		RE MADE I	N THE	
B. THE ABOVE NUMBERED CONTRACT				uch as chang	es in paying	g
office, appropriation date, etc.) SET FO: C. THIS SUPPLEMENTAL AGREEMENT			AR 43.103(B).			
D. OTHER (Specify type of modification ar	nd authority)					
E. IMPORTANT: Contractor is not,	is required to sig	gn this document and return	copies to the issui	ng office.		
14. DESCRIPTION OF AMENDMENT/MODI where feasible.) The above numbered solicitation for Lake Pontage Canal Closure Structure, Orleans Parish, L	ontchartrain, LA & Vic	inity, New Orleans Area Plan Emerger		-		
Proposal date of 22 January 2006 10:00 a.m	., local time and place	e remains unchanged.				
·	·	-				
Except as provided herein, all terms and conditions of the						
15A. NAME AND TITLE OF SIGNER (Type	or print)	16A. NAME AND TITLE OF CO	ONTRACTING OF	FICER (Typ	e or print)	
		TEL:	EMAIL:			
15B. CONTRACTOR/OFFEROR	15C. DATE SIGNE	D 16B. UNITED STATES OF AME	RICA	160	C. DATE SI	iGNED
		ВУ			0 lan 2006	2
(Signature of person authorized to sign)	_	(Signature of Contracting Of	fficer)	^	0-Jan-2006	,

SECTION SF 30 BLOCK 14 CONTINUATION PAGE

- 1.) 00010 Bid Sheet. Revise Bid Item 20 "Piling, Steel Sheet, Type PS 27.5" to have an Estimated Quantity of 52,000 SF.
- 2.) Spec. Section 03308-1.6.3.1. Change the third sentence in the paragraph to read as follows "The air content shall be between 3.5 percent to 7.5 percent."
- 3.) Delete the note at the end of TABLE 1, Section 03308-29 and replace with the following revised note:

NOTE: The estimated tremie concrete mixture proportions presented in the table are based on a preliminary mixture design and initial trial batch testing. The mixture proportions are primarily for estimating the bid price of the contract. The actual tremie concrete design shall be provided by the Contractor to the Government. Alternatively, the Contractor may propose a concrete mixture design to be used for the tremie concrete. Silica Fume and Limestone Powder are not requirements provided the mix meets the criteria for slump, strength and the other parameters listed in paragraph 1.6.3.2.

4.) Delete Spec Section 15200-2.1.2 and replace with the following:

2.1.2 Flanged Fittings

Flanges shall be fabricated in accordance with the requirements of AWWA C207, Steel Ring Flanges, Class D, dimensions as shown in Table 2. Steel used to fabricate the flanges shall meet the requirements of ASTM A516, any grade.

5.) Delete spec section 15200-2.1.1 in its entirety and replace with the following

"2.1.1 Steel Pipe

Steel pipe and elbows shall be fabricated in accordance with the requirements of AWWA C200, except hydrostatic testing is not required. Dimensions of elbows shall meet the requirements of AWWA C208. Steel used to fabricate pipe and elbows shall be any of the specifications listed in Table 1 of AWWA C200, except the minimum yield point shall be 50,000 pounds per square inch or greater. Pipe shall not be helical or spiral seamed. Pipe wall thickness shall 5/8"

6.) Delete spec section 15200-2.2 in its entirety and replace with the following

2.2 PIPE FABRICATION

The Contractor shall fabricate pipe in accordance with AWWA C200 except the hydrostatic testing requirement is waived. Weld shall be performed and inspected as specified in accordance with Section 05093-3.2. Pipe shall be shipped to site in one piece with flanges attached (on each side, flood and protected). Field welding shall not be performed. Lifting lugs shall be attached for handling and installation. Lifting lugs may be left in place.

7.) Delete the note at the end of TABLE 1, Section 03308-29 and replace with the following revised note:

NOTE: The estimated tremie concrete mixture proportions presented in the table are based on a preliminary mixture design and initial trial batch testing. The mixture proportions are primarily for estimating the bid price of the contract. The actual tremie concrete design will be provided to the Contractor by the Government. Alternatively, the Contractor may propose a concrete mixture design to be used for the tremie concrete. Silica Fume and Limestone Powder are not requirements provided the mix meets the criteria for slump, strength and the other parameters listed in paragraph 1.6.3.2.

- 8.) Spec Section 05120-1.1.3 Add the following sentence to the end of the paragraph, "Steel H-Piles shall be measured and paid for as specified in Section 02315 "Steel H-Piles and Sheet Piling"
- 9.) Drawing 10 of 20. Revise the note located under the Plan View to read "6 Units Required"